

What is claimed is:

1. A splint for immobilizing and supporting a limb of a human or other body parts, said splint is made of flexible material for covering said limb and limb articulation from three sides wherein a part of the limb remains uncovered, said splint includes:

- a) inflatable tubes interconnected by non-inflatable parts for achieving variable degrees of support, stiffness and restriction of movement;
- b) ventilation holes for skin ventilation contained in the non-inflatable parts;
- c) at least one gas pressure source device connected to said splint;
- d) at least one adjustable surface for connecting splint edges;
- e) at least one loop connected to the edge of said splint for suspension purposes.

wherein the inflated structure of the splint fits the structure of the appropriate body part for the purpose of stabilizing and providing support to the patient's body part and its articulations in varying degrees of rigidity and in particular positions.

2. The splint according to claim 1, wherein the adjustable straps are made of Velcro.

3. The splint according to claim 1, wherein said splint is designed to wrap the torso, taking into account the structure of the body and its curves for maximum compatibility.

4. The splint according to claim 1, wherein said splint is designed to wrap to the neck, taking into account the neck's curves and structure for maximum compatibility.

5. The splint according to claim 1, wherein said splint is designed to wrap the leg, the foot, the ankle and the heel of the patient, taking into account the leg's curves and structure for maximum compatibility and preventing pressure on the heel.

5. The splint according to claim 1, wherein said splint is designed to wrap the arm, fit the shoulder structure, support the palm taking into account the arm's curves and structure for maximum compatibility and immobilizing the shoulder joints or upper and lower arm in any desired position.

6. The splint according to claim 1, wherein said splint is made of two nylon layers joined together by soldering means.

7. The splint according to claim 1, wherein said splint is made of two nylon layers which are coated with polyurethane.
8. The splint according to claim 1, wherein movement, rigidity and stabilization of said limb articulation is controlled by the degree of air pressure in said splint.
9. The splint according to claim 1, wherein the pressure source device is a hand pump.
10. The splint according to claim 1 wherein in the inflated state the splint takes up the shape of the body part for which it was designed.
11. The splint according to claim 1 wherein the tightness of the splint on the body part is controlled by the fastening or loosening of the Velcro straps.
12. The splint according to claim 1 further including a suspension strap.
13. The splint according to claim 1 wherein pressure within the splint is controlled by a valve.
14. The splint according to claim 1 wherein the adjustable strap is detachable.